

IN THE CLAIMS

Please amend the claims as follows:

1. (Original) A method for jamming communications between a medical device and an external device to prevent data transfer, the method comprising the steps of
receiving an external input at a blocking device to begin jamming the communications between the medical device and the external device; and
transmitting a jamming signal from the blocking device to jam the communications between the medical device and the external device.
2. (Original) The method of claim 1, wherein the blocking device is a short range jamming transmitter.
3. (Original) The method of claim 1, wherein the jamming signal blankets the frequency range used for the communications.
4. (Original) The method of claim 2, wherein the short range jamming transmitter is in proximity to the medical device and wherein transmitting a jamming signal from the blocking device to jam the communications comprises preventing the medical device from receiving a solicitation to begin transmitting that is sent by the external device.
5. (Original) The method of claim 1, wherein the communications occur through a cellular phone system employing control channels and the jamming signal blankets the control channels used for the communications.
6. (Original) The method of claim 1, wherein the input is received in response to manipulating a user interface at the blocking device.

7. (Original) The method of claim 1, further comprising providing an indication of jamming, wherein the indication is a visual indication on the blocking device.

8. (Original) The method of claim 1, further comprising providing an indication of jamming, wherein the indication is an auditory signal transmitted by the blocking device.

9. (Original) The method of claim 1, further comprising the steps of determining whether a predetermined period of time has passed and, if so, then ceasing to transmit the jamming signal.

10. (Original) The method of claim 1, wherein the communications comprise communications related to electively recorded physiological patient data.

11. (Currently Amended) A method for inhibiting communications between a medical device and an external device to prevent data transfer, the method comprising the steps of:

receiving an external input to begin inhibiting the communications between the medical device and the external device, wherein the medical device is an implantable medical device; and
upon receiving the input, ceasing to establish data transmission of the data generated from the medical device.

12. (Original) The method of claim 11, wherein the input is received at the external device and ceasing data transfer comprises ceasing sending a solicitation for data from the external device to the medical device.

13. (Original) The method of claim 11, wherein the input is received at a blocking device and wherein ceasing data transmission comprises sending a communication from the blocking device to the external device instructing the external device to cease sending a solicitation for data to the medical device.

14. (Original) The method of claim 13, further comprising generating an indication of inhibited communications, wherein the indication is a visual indication on the blocking device.

15. (Original) The method of claim 13, further comprising generating an indication of inhibited communications, wherein the indication is an auditory signal transmitted by the blocking device.

16. (Original) The method of claim 11, further comprising the steps of determining whether a predetermined period of time has passed and, if so, then no longer ceasing to establish data transmission from the medical device to the external device.

17. (Original) The method of claim 11, wherein the data transmission comprises communications related to electively recorded physiological patient data.

18. (Original) The method of claim 11, wherein the input is received at the external device and wherein ceasing to establish data transmission comprises stopping reception of communications from the medical device at the external device.

19. (Original) The method of claim 11, wherein the input is received at the medical device through a sensor and wherein ceasing to establish data transmission comprises stopping transmitting of communications from the medical device.

20. (Original) The method of claim 19, wherein the input comprises a signal at an accelerometer of the medical device.

21. (Original) The method of claim 20 wherein the signal received at the accelerometer comprises a series of taps on the patient's body.

22. (Original) The method of claim 11, wherein the input is received at a blocking device and wherein ceasing to establish data transmission comprises transmitting an instruction from the blocking device to the medical device to cease transmission.

23–34. (Cancelled)

35. (Currently Amended) A method for inhibiting communications involving data generated at [[a]] an implantable medical device between a local external device and a remote external device to prevent data transfer, the method comprising the steps of:

receiving a data transmission from the implantable medical device at the local external device;

receiving an external input to begin inhibiting the communications between the local external device and the remote external device; and

upon receiving the input, ceasing to establish data transmission from the local external device to the remote external device to inhibit communication of information between the implantable medical device and the remote external device.

36. (Original) The method of claim 35, wherein the input is received at the local external device to stop the local external device from transmitting the data transmission from the medical device to the remote external device.

37. (Original) The method of claim 35, wherein the input is received at a blocking device and wherein ceasing to establish data transmission comprises sending a signal from the blocking device to the local external device instructing the local external device to not forward the data transmission from the medical device to the remote external device.

38. (Currently Amended) A medical device, comprising:
a communications system that sends and receives signals;
at least one sensor that detects physiological information about a patient to produce data;

a controller configured to detect an input at the at least one sensor indicating that data transmission should cease, and to cease transmitting data through the communication system upon detecting the input.

39. (Original) The medical device of claim 38, wherein the at least one sensor comprises an accelerometer, and wherein the input is a signal from the accelerometer resulting from taps by a patient wearing the medical device.

40. (Original) The medical device of claim 38, further comprising a timer, and wherein the controller detects from the timer the amount of time that data transmission has ceased and restarts data transmission upon the expiration of a pre-defined interval.

41. (Original) The medical device of claim 38, wherein the input is a signal received through the communications system.

42–45. (Cancelled)

46. (Currently Amended) An external repeater device for communicating with [[a]] an implantable medical device, comprising:

a communications system that sends and receives signals such that patient data is received from the implantable medical device upon a solicitation for data being sent from the communications system;

a controller configured to detect an input indicating that data transmission should cease, and to cease transmitting the solicitation for data through the communications system to the implantable medical device upon detecting the input.

47. (Cancelled)

48. (Currently Amended) A blocking device for preventing [[a]] an implantable medical device from transferring data, comprising a transmitter generating a blocking signal that is received by the implantable medical device, and wherein the blocking signal being received at the implantable medical device results in no transfer of data from the implantable medical device.

49. (Original) The blocking device of claim 48, wherein the blocking signal is a jamming signal that is generated during a period of time when a solicitation signal is being sent to the medical device, and wherein reception of the jamming signal blocks reception of the solicitation signal by the medical device.

50. (Currently Amended) A system for inhibiting communications between [[a]] an implantable medical device and an external device to prevent data transfer, the system comprising:

means for receiving an external input to begin inhibiting the communications between the implantable medical device and the external device; and

means for, upon receiving the input, ceasing to establish data transmission of the data generated from the implantable medical device.

51. (New) The method of claim 1, in which the jamming signal is operable to prevent reception of communications by the medical device.

52. (New) The method of claim 51, in which the jamming signal is operable to prevent reception of communications by the medical device that are intended to cause the medical device to begin transmitting data.